



同步轮/同步带/免键轴衬

免键轴衬

标准型(带定心功能)



型号(①代码·②d)
CBLM35



型号区分: 代码 5 天发货





CBLM

CBLMB (发黑)

CBLMP (无电解镀镍)

CBLHS (不锈钢)



代码	主体	
	材质	表面处理
CBLM	S45C	—
CBLMB		发黑
CBLMP		无电解镀镍
CBLHS	SUS304	—

■ 导向轴及联轴器的推荐公差、表面粗糙度

安装面	公差	表面粗糙度
轴外径	h7(g6)	Ra1.6以下
轮孔内径	H7	Ra3.2以下

型号		D	D ₁	P.C.D.	L ₂	L ₃	T	T ₂	锁紧螺栓		
① 代码	② d								M×L	个数	
CBLM CBLMB (发黑) CBLMP (无电解镀镍) CBLHS (不锈钢)	5	16	18.5	11.7	13	8	1.8	1.2	M3×10	4	
	6	19	21.5	14	14.3	9	2.0	1.3	M4×12		
	8	21	23.5	15.4	14.6	9.3	2.0	1.3			
	10	23	25.5	17.5	14.8	9.5					
	11	24	26.5	18.4	15.8	18.0	10.5	2.5	1.5	M4×15	6
	12	26	28.5	20.2	20.1						
	14	28	30.5	22.2		19.0	11.5				
	15	29	31.5	23.2				19.6	12.0		
	16	30	33.0	24.2	24.1	15.3	1.6				
	17	31	33.5	25.2				3.0	1.8		
	18	32	34.5	26.2			17.3			3.5	
	19	33	35.5	27.2				26.6	21.0		
	20	38	42.0	30.8	27.6	18.3	M5×18			8	
	22	40	44.0	32.8				30.0	19.5		
	24	42	46.0	34.8	25.1	16.3					4.0
	25	43	47.0	35.8	26.1	21.0		4.5			
	28	46	50.0	38.8	32.0		21.5		5.0		
	30	48	52.0	40.8		32.5		22.0			
	32	50	54.0	42.8	33.5		22.0		M8×25	14	
	35	57	62.0	48.4		30.0		19.5			
38	60	65.0	51.4	30.5	20.0						
40	62	67.0	53.4	31.0	20.5	4.0					
42	64	69.0	55.4				31.5	21.0			
45	67	72.0	58.4	32.0	21.5	4.5					
48	70	75.0	61.4				32.5	21.5	5.0		
50	72	77.0	63.4	33.5	22.0	M6×20				12	
55	77	83.0	68.4				32.5	21.5	4.5		
60	82	87.0	73.4	33.5	22.0						5.0
65	87	92.0	78.4				36.1	24.0	5.0		
70	97	103.0	86.2	36.1	24.0	5.0					