



D公差 (g6)		代码		材质	硬度	表面处理	附件	
		L尺寸固定型	L尺寸指定型					
3	-0.002 -0.008	BDHMG	BDHLGN	S45C	—	发黑	1个开口销	SWRM
4~6	-0.004 -0.012	BDHMGH	BDHLGHN		40~45HRC			
8·10	-0.005 -0.014	—	BDPHLGN		—	无电解镀镍		
		—	BDPHLGHN		40~45HRC			
12~16	-0.006 -0.017	—	BDGHLGN	镀层硬度750HV~	镀硬铬	SWRM		
		BDSHMG	BDSHLGN	SUS304				—
20·25	-0.007 -0.020	—	BDSHLGHN	SUS440C	45~50HRC	—	SUS304	
		—	BDGSHLGHN	—	45~50HRC 镀层硬度750HV~			镀硬铬

$\frac{25}{\sqrt{}} \left(\frac{16}{\sqrt{}} \right)$

选型示范

型号(①代码·②D) — ③L

BDHMG8 — 30

BDHLGN15 — 90.3

■请按步骤①~③选择
型号和参数后进行订购。

交货期

型号区分: 代码 **7** 天发货

■L尺寸固定型

型号		③L 选择	L ₁	N	u	(n)	d	T	H
① 代码	② D								
BDHMG BDHMGH (淬火型) BDSHMG	3	10 12 14 15 16 18 20	L+4.4	2.5	2.9	1.5	0.8	1.5	5.5
	4		L+4.5		3.9		1		6.5
	5	15 16 18 20 22 24 25 30	L+5.6	3.5	4.9		1.2		8
	6		L+5.8		5.8		1.6		9
	8	18 20 22 24 25 30 35 40 45 50	L+7	4	7.8		2	2	12
	10		L+8.25	5	9.8		2.5		14
	12	22 24 25 30 35 40 45 50	L+10.6	6	11.8		3.2	3	17

■L尺寸指定型 (最小单位0.1mm)

型号		③L 最小单位 0.1mm	L ₁	N	u	(n)	d	T	H
① 代码	②D								
BDHLGN BDHLGHN BDPHLGN BDPHLGHN BDGHLGN BDSHLGN BDSHLGHN BDGSHLGHN	3	5.0~ 50.0	L+4.4	2.5	2.9	1.5 以下	0.8	1.5	5.5
	4		L+4.5		3.9		1		6.5
	5	10.0~ 60.0	L+5.6	3.5	4.9		1.2		8
	6		L+5.8		5.8		1.6		9
	8	10.0~100.0	L+7	4	7.8		2	2	12
	10		L+8.25	5	9.8		2.5		14
	12	15.0~150.0	L+10.6	6	11.8		3.2	3	17
	15		L+12	7	14.8		4		20
	16	20.0~150.0			15.8				21
	20	20.0~150.0	L+14.5	8	19.8		5	4	26
	25		L+15.5	9	24.8				30