



型号			④ 齿数	皮带宽度 (mm)	容许张力(N)		适用连接金属件	
① 代码	② 皮带类型	③ 皮带公称宽度			氯丁橡胶	聚氨酯		
CBOG (精密型 氯丁橡胶)	XL	025	50~3000	6.4	30	65	CBCK-XL025	
		037		9.5	45	100	CBCK-XL037	
		050		12.7	70	140	CBCK-XL050	
	L	050		12.7	95	260	CBCK-L050	
		075		19.1	165	390	CBCK-L075	
		100		25.4	225	520	CBCK-L100	
	H	075		19.1	175	400	CBCK-H075	
		100		25.4	235	530	CBCK-H100	
		150		38.1	345	800	CBCK-H150	
	200	50.8		465	1095	CBCK-H200		
	CBOG (精密型 氯丁橡胶)	S3M		060	6	65	130	CBCK-S3M060
				100	10	70	105	CBCK-S3M100
150				15	90	160	CBCK-S3M150	
S5M		100		10	213	305	CBCK-S5M100	
		150		15	322	488	CBCK-S5M150	
		250		25	340	540	CBCK-S5M250	
S8M		150		15	485	650	CBCK-S8M150	
		250		25	950	1175	CBCK-S8M250	
		300		30	1065	1410	CBCK-S8M300	
400		40		1325	1880	CBCK-S8M400		
CBOH/CBOI (精密型聚氨酯)		T5		100	10	—	110	CBCK-T5100
				150	15		165	CBCK-T5150
	200			20	225		CBCK-T5200	
	T10	250		25	285		CBCK-T5250	
		150		15	300		CBCK-T10150	
		200		20	400		CBCK-T10200	
		250		25	530		CBCK-T10250	
		300		30	625		CBCK-T10300	
		400		40	860		CBCK-T10400	
		500		50	1065		CBCK-T10500	

① 全长计算公式=齿数×齿距。